



**ATTIC COVERAGE CHART – ALL BORATE STABILIZED CLASS 1 FIRE RATED MATERIAL**

Installed Density and Coverage of FRM			FRM100
SF PER BAG			
Target Finished Density (Dry pcf)	8" Cavity	12" Cavity	Minimum Finished Density (Dry pcf)*
4.0	12.0	7.5	3.35

\*IF ANY PART OF THE ASSEMBLY HAS A DRY (10% OR LESS MOISTURE BY WEIGHT) DENSITY LESS THAN 3.35 PCF, THE WALL IS NO LONGER AN APPROVED UL TWO HOUR FIRE ASSEMBLY.

**READ THIS BEFORE YOU BUY** WHAT YOU SHOULD KNOW ABOUT R-VALUES

This chart shows the R-Value of this insulation. R means resistance to heat flow. The higher the R-Value, the greater the insulating power. Compare insulation R-Values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-Value, it is essential that this insulation be installed properly.

Manufactured by  
**Greenfiber®**

Toll-Free 800-228-0024  
www.greenfiber.com

Greenfiber® is a registered trademark of Greenfiber®  
© 2023 Greenfiber®.

All rights reserved.  
Greenfiber®  
5500 77 Center Drive,  
Suite 100 Charlotte, NC 28217

Made in USA

Decatur, AL 35601  
Tampa, FL 33605  
Eastanollee, GA 30538  
Hickory, KY 42051  
Webberville, MI 48892  
Lester Prairie, MN 55354  
Norfolk, NE 68701  
Chambersburg, PA 17201  
Wilkes Barre, PA 18702  
Waco, TX 76704  
Salt Lake City, UT 84119  
Debert, Nova Scotia  
Chandler, AZ 85225



UL Classified  
See complete marking on back of packaging



**Seal and Insulate with ENERGY STAR**  
Insulation saves energy when installed according to ENERGY STAR guidelines.  
LEARN MORE AT energystar.gov